

### MAYER FABRICS

**FORTE (MAYER FABRICS):**



**FORTE:**

CONTENT: 100% Polyester  
 WIDTH: 54 inches / 137cm  
 BACKING: Acrylic  
 APPROX REPEAT: None  
 WEIGHT: 12.10oz./linear yard / 375.14g/lm  
 FINISH: Stain Repellent  
 DIRECTIONAL: No  
 RAILROADED: No

SURFACE ABRASION: Heavy Duty ASTM D 4157  
 PILING RESISTANCE: ASTM D 3511

COLORFASTNESS to COCKING: AATCC 8  
 COLORFASTNESS to LIGHT: AATCC 16

PASSES: 183,000 Double Rubs  
 CLASS: 5  
 DRY: Class 4 min / Wet: Class 4  
 CLASS: 5 at 40 hours

FLAMMABILITY : California Technical Bulletin 117-2013  
 NFPA 260/UFAC Class 1  
 ASTM E84 (Adheard) Class 2 or B  
 May comply with California Technical Bulletin 133 when combined with appropriate components.

## SILVERTEX™ (ENNIS FABRICS):

\*\*Specific colour options listed below require a minimum lead time of two weeks.



## SILVERTEX™ (ENNIS FABRICS):

CONTENT: Vinyl  
 BACKING: Hi-Loft™ 100% Polyester  
 FINISHES: PERMABLOK®  
 ANTIBACTERIAL: ATCC TM 147  
 ANTISTATIC: ASTM D-257

MILDEW RESISTANT: ASTM G21  
 STAIN RESISTANT  
 NO HEAVY METALS  
 FORMALDEHYDE FREE  
 NO FLAME RETARDANTS  
 PROP 65 COMPLIANT

SUPERIOR ABRASION: CFFA L-A / ASTM D-4157 1000 Cycles, Wyzenbeek #10 Cotton Duck  
 COLD CRACK -10°F: CFFA-6-a  
 CROCKING RESISTANCE: CFFA-7 ATCC TM 8: Pass

WEIGHT: 30oz  
 WIDTH: 54in  
 ROLL SIZE: 30yd

FLAME RETARDANCY\*  
 California T.B 117 - 2013  
 NFPA 260 - Class I  
 UFAC - Class I

### APPLICATIONS:

- EDUCATION
- HEALTHCARE
- OFFICE
- HOSPITALITY
  - Hotel | Motel | Casino
  - Resturant
  - Theatres | Convention Centers
- MARINE
  - Interior & Exterior
- RESIDENTIAL
  - Interior & Exterior



### CHALLENGER VINYL (ENNIS FABRICS):



### CHALLENGER:

- CONTENT: 100% Polyvinyl Chloride (PVC)
- BACKING CONTENT: 100% Polyester
- ABRASION: Exceeds 1,500,000 Double Rubs
- FINISH: Endurepel Armour
- COLD CRACK: -55°C (-67°F)
- TEAR STRENGTH: ASTM D2261: Warp = 10 lbs Weft = 13 lbs
- TENSILE STRENGTH: ASTM D5034: Warp = 101 lbs Weft = 94 lbs
- UV/LIGHT FASTNESS: AATCC 16.3 - Grade 4 (1500 Hrs)
- ELONGATION: ASTM D571: Warp = 64%, Weft = 116%
- FIRE RETARDANCY\*: CALTB117-2013, IMO FTP Code 2010 - Part 8  
MVSS 302, NFPA 260 Class 1, UFAC Class 1
- WEIGHT: 736 Grams per Square Meter  
33.17 Ounces per Linear Yard  
21.71 Ounces per Square Yard
- WIDTH: 55" (140 cm)
- ROLL SIZE: 30 Yards (27 m)
- CLEANING INSTRUCTIONS: W - Clean fabrics with water-based cleaning agents or water based foam. Dilution ratios must be followed. Materials must be wiped with clean water after use and wiped dry with a clean cloth.