PALMIER CLASSIC

 MODEL NUMBER	PRODUCT	W	D	Н	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
AP-MC-36-SS AP-MC-36-SA AP-MC-48-SS AP-MC-48-SA	Single Face Modular Carrels: 36" Starter 36" Adder 48" Starter 48" Adder	38 ¹ /2" 36 ¹ /4" 50 ¹ /2" 48 ¹ /4"	31" 31" 31" 31"	48" 48" 48" 48"	340 Lbs. 160 Lbs. 360 Lbs. 190 Lbs.	11 Cu Ft 11 Cu Ft 11 Cu Ft 11 Cu Ft	\$ 5,138 \$ 3,382 \$ 5,293 \$ 3,536	WORK SURFACE: Tops are constructed of 1 ¹ /4" thick 3-ply particleboard core. Tops surface is laminated with a .050" thick high pressure plastic laminate sheet and bottom surface laminated with a backing sheet not less than .020" thick for balanced construction. Front work surface edge is ³ /4" thick x 1 ⁵ /8" high solid hardwood with edges eased. Work surface is 28" deep x 29"high.
AP-MC-36-DS AP-MC-36-DA AP-MC-48-DS AP-MC-48-DA	Double Face Modular Carrels: 36" Starter 36" Adder 48" Starter 48" Adder	38 ¹ /2" 36 ¹ /4" 50 ¹ /2" 48 ¹ /4"	60 ¹ /2" 60 ¹ /2" 60 ¹ /2" 60 ¹ /2"	48" 48" 48" 48"	655 Lbs. 250 Lbs. 710 Lbs. 310 Lbs.	22 Cu Ft 22 Cu Ft 22 Cu Ft 22 Cu Ft	\$ 7,175 \$ 4,556 \$ 7,392 \$ 4,781	END PANELS: Panel frame construction consists of a 1 ¹ / ₁₆ " thick 3-ply particleboard core with plain sliced veneer both faces, 1 ³ / ₄ " thick x 2 ¹ / ₂ " wide solid hardwood framed on four sides and three inset 1/ ₂ "thick x 1 ³ / ₄ " wide solid vertical pilasters. All edges of panel frame and pilasters are eased. Single face and pinwheel shall receive three vertical pilasters and double face shall receive five vertical pilasters. INTERMEDIATE PANELS: Panels are constructed of 1 ³ / ₁₆ " thick 3-ply particleboard core with plain sliced veneer both faces, 1 ³ / ₁₆ " thick x 2 ¹ / ₂ " wide solid hardwood framed on four sides with all edges eased.
								BACK PANEL: Back is constructed of $1^1/16^n$ thick 3-ply particleboard core with plain sliced veneer both faces and the top edge is banded with a $1^1/16^n$ thick x $2^1/4^n$ wide solid hardwood.
AP-MC-36-PW AP-MC-48-PW	36" Pinwheel 48" Pinwheel	74 ¹ /2" 91 ¹ /2"	74 ¹ /z" 91 ¹ /z"	48" 48"	780 Lbs. 800 Lbs.	48 Cu Ft 55 Cu Ft	\$ 11,862 \$ 12,282	TOP SHELF: Shelf construction consists of ³ / ₄ " thick 3-ply particleboard core with plain sliced veneer both faces and the front edge is banded with a ¹ / ₄ " solid external edge complete with a ³ / ₄ " thick x 1 ¹ / ₂ " wide solid hardwood valance rail mounted to the underside. Shelf is 10" deep positioned 15 ¹ / ₂ " above the work surface.



PALMIER CLASSIC

 MODEL NUMBER	PRODUCT	W	D	Н	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
AP-RC-36-SS AP-RC-36-SA AP-RC-48-SS AP-RC-48-SA	Single Face Reference Carrels: 36" Starter 36" Adder 48" Starter 48" Adder	38 ¹ /2" 36 ¹ /4" 50 ¹ /2" 48 ¹ /4"	31" 31" 31" 31"	48" 48" 48" 48"	340 Lbs. 160 Lbs. 360 Lbs. 190 Lbs.	11 Cu Ft 11 Cu Ft 11 Cu Ft 11 Cu Ft	\$ 5,256 \$ 3,374 \$ 5,411 \$ 3,521	WORK SURFACE: Tops are constructed of 11/4" thick 3-ply particleboard core. Tops surface is laminated with a .050" thick high pressure plastic laminate sheet and bottom surface laminated with a backing sheet not less than .020" thick for balanced construction. Front work surface edge is 3/4" thick x 15/8" high solid hardwood with edges eased. Tops will be set back from the back panel 2" to provide a wire drop and will be fitted with a retainer lip. Work surface is 26" deep and is adjustable at four increments 39", 32", 29" and 27" high.
AP-RC-36-DS AP-RC-36-DA AP-RC-48-DS AP-RC-48-DA	Double Face Reference Carrels: 36" Starter 36" Adder 48" Starter 48" Adder	38 ¹ /2" 36 ¹ /4" 50 ¹ /2" 48 ¹ /4"	60 ¹ /2" 60 ¹ /2" 60 ¹ /2" 60 ¹ /2"	48" 48" 48" 48"	655 Lbs. 250 Lbs. 710 Lbs. 310 Lbs.	22 Cu Ft 22 Cu Ft 22 Cu Ft 22 Cu Ft 22 Cu Ft	\$ 7,159 \$ 4,532 \$ 7,369 \$ 4,758	END PANELS: Panel frame construction consists of a 1 ¹ / ₁₆ " thick 3-ply particleboard core with plain sliced veneer both faces, 1 ³ / ₄ " thick x 2 ¹ / ₂ " wide solid hardwood framed on four sides and three inset ¹ / ₂ " thick x 1 ³ / ₄ " wide solid vertical pilasters. All edges of panel frame and pilasters are eased. Single face and pinwheel shall receive three vertical pilasters and double face shall receive five vertical pilasters. INTERMEDIATE PANELS: Panels are constructed of 1 ³ / ₁₆ " thick 3-ply particleboard core with plain sliced veneer both faces, 1 ³ / ₁₆ " thick x 2 ¹ / ₂ " wide solid hardwood framed on four sides with all edges eased.
								BACK PANEL: Back is constructed of $1^{1}/_{16}$ " thick 3-ply particleboard core with plain sliced veneer both faces and the top edge is banded with a $1^{1}/_{16}$ " thick x $2^{1}/_{4}$ " wide solid hardwood.
AP-RC-36-PW	36" Pinwheel	741/2"	74 ¹ /2"	48"	780 Lbs.	48 Cu Ft	\$ 11,831	BOTTOM SHELF:
AP-RC-48-PW	48" Pinwheel	911/2"	91 1/2"	48"	800 Lbs.	55 Cu Ft	\$ 11,986	Shelf construction consists of $^3/^a$ " thick 3-ply particleboard core with plain sliced veneer both faces and the front edge is banded with a $^1/^a$ " solid external edge complete with a $^3/^a$ " thick x $^11/^a$ " wide solid hardwood valance rail mounted to the underside. Shelf is 10" deep positioned 21" above the floor.

