

	MODEL NUMBER	PRODUCT	W	D	Н	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
		Single Face Modular Carrels							WORK SURFACE:
		Version 1:							Tops are constructed of $1^{1}/4^{\circ}$ thick 3-ply particleboard core.
	FS-SC-V1-36-SS	36" Starter	37 ¹ /2"	31"	36"	180 Lbs.	10 Cu Ft	\$ 3,049	Top surface is laminated with a .050" thick high pressure
THE RESERVE TO SERVE AND ADDRESS OF THE PARTY OF THE PART	FS-SC-V1-36-SA	36" Adder	36"	31"	36"	130 Lbs.	7 Cu Ft	\$ 2,704	plastic laminate sheet and bottom surface laminated with
	FS-SC-V1-48-SS	48" Starter	49 ¹ /2"	31"	36"	200 Lbs.	11 Cu Ft	\$ 3,164	a backing sheet not less than .020" thick for balanced
	FS-SC-V1-48-SA	48" Adder	48"	31"	36"	160 Lbs.	8 Cu Ft	\$ 2,812	construction. Front work surface edge is ³ / ₄ " thick x 1 ¹ / ₄ " high
									solid external hardwood with 1/2" radius at the top and eased
									at the bottom. Work surface is 28" deep x 29" high.
									END AND MID PANELS:
									Panel construction consists of a 1 ¹ /16" thick 3-ply particleboard
									core with plain sliced veneer both faces and 1/4" thick solid top
									and bottom edge. Front and back edge machined to receive
									$1^{1}/2^{\circ}$ x $1^{1}/2^{\circ}$ tubular, 16 gauge steel posts.
		Double Face Modular Carrels							
		Version 1:							BACK PANEL:
	FS-SC-V1-36-DS	36" Starter	37 ¹ /2"	62"	36"	255 Lbs.	14 Cu Ft	\$ 4,197	Back is constructed of 1 ¹ / ₁₆ " thick 3-ply particleboard core with
	FS-SC-V1-36-DA	36" Adder	36"	62"	36"	160 Lbs.	11 Cu Ft	\$ 3,698	plain sliced veneer both faces, 1/4" solid hardwood at top and
	FS-SC-V1-48-DS	48" Starter	491/2"	62"	36"	290 Lbs.	16 Cu Ft	\$ 4,394	bottom with eased edges.
	FS-SC-V1-48-DA	48" Adder	48"	62"	36"	210 Lbs.	12 Cu Ft	\$ 3,900	





MODEL NUMBER	PRODUCT	W	D	Н	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
FS-SC-V2-36-SS FS-SC-V2-36-SA FS-SC-V2-48-SS FS-SC-V2-48-SA	Single Face Modular Carrels Version 2: 36" Starter 36" Adder 48" Starter 48" Adder	37 ¹ /2" 36" 49 ¹ /2" 48"	31" 31" 31" 31"	36" 36" 36" 36"	180 Lbs. 130 Lbs. 200 Lbs. 160 Lbs.	10 Cu Ft 7 Cu Ft 11 Cu Ft 8 Cu Ft	\$ 3,407 \$ 2,926 \$ 3,515 \$ 3,042	WORK SURFACE: Tops are constructed of 1 ¹ / ₄ " thick 3-ply particleboard core. Top surface is laminated with a .050" thick high pressure plastic laminate sheet and bottom surface laminated with a backing sheet not less than .020" thick for balanced construction. Front work surface edge is ³ / ₄ " thick x 1 ¹ / ₄ " high solid external hardwood with ¹ / ₂ " radius at the top and eased at the bottom. Work surface is 28" deep x 29" high.
	Double Face Modular Carrels Version 2:							END AND MID PANELS: Panel construction consists of a 1 ¹ / ₁₆ " thick 3-ply particleboard core with plain sliced veneer both faces. Upper portion is fitted with ¹ / ₄ " thick frosted acrylic screen and ¹ / ₄ " thick solid bottom edge. Front and back edge machined to receive 1 ¹ / ₂ " x 1 ¹ / ₂ " tubular, 16 gauge steel posts.
FS-SC-V2-36-DS FS-SC-V2-36-DA FS-SC-V2-48-DS FS-SC-V2-48-DA	36" Starter 36" Adder 48" Starter 48" Adder	37 ¹ /2" 36" 49 ¹ /2" 48"	62" 62" 62" 62"	36" 36" 36" 36"	255 Lbs. 160 Lbs. 290 Lbs. 210 Lbs.	14 Cu Ft 11 Cu Ft 16 Cu Ft 12 Cu Ft	\$ 4,806 \$ 4,049 \$ 5,009 \$ 4,251	BACK PANEL: Back is constructed of 1 1/16" thick 3-ply particleboard core with plain sliced veneer both faces, 1/4" solid hardwood at top and bottom with eased edges.



core with plain sliced veneer both faces and the front edge is banded with a 1/4" solid external edge. Shelf is 12" deep

positioned 21" above the floor.

 MODEL NUMBER	PRODUCT	W	D	Н	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
_								
	Single Face Reference Carrels:							WORK SURFACE:
FS-RC-36-SS	36" Starter	37 ¹ /2"	31"	48 ¹ /2"	200 Lbs.	10 Cu Ft	\$ 3,319	Tops are constructed of $1^{1}/4^{\circ}$ thick 3-ply particleboard core.
FS-RC-36-SA	36" Adder	36 ¹ /4"	31"	48 ¹ /2"	150 Lbs.	7 Cu Ft	\$ 2,941	Top surface is laminated with a .050" thick high pressure
FS-RC-48-SS	48" Starter	491/4"	31"	48 ¹ /2"	230 Lbs.	11 Cu Ft	\$ 3,448	plastic laminate sheet and bottom surface laminated with
FS-RC-48-SA	48" Adder	481/4"	31"	481/2"	180 Lbs.	8 Cu Ft	\$ 3,069	a backing sheet not less than .020" thick for balanced construction. Front work surface edge is ³ / ₄ " thick x 1 ¹ / ₄ " high solid external hardwood with ¹ / ₂ " radius at the top and eased at the bottom. Tops will be set back from the back panel 2" to provide a wire drop and will be fitted with a retainer lip. Work surface is 26" deep and is adjustable at four increments 39", 32", 29" and 27" high.
_	Double Face Reference Carrels:							END AND MID PANELS:
FS-RC-36-DS	36" Starter	37 ¹ /2"	60 ¹ /2"	48 ¹ / ₂ "	275 Lbs.	14 Cu Ft	\$ 4,530	Panel frame construction consists of a 1 ¹ /16" thick 3-ply particleboard core with plain sliced veneer both faces and
FS-RC-36-DA	36" Adder	36 ¹ /4"	60 / 2 "	48 ¹ /2"	180 Lbs.	11 Cu Ft	\$ 4,550	¹ /4" thick solid top and bottom edge. Front and back edge
FS-RC-48-DS	48" Starter	49 ¹ / ₄ "	60 ¹ /2"	48 ¹ /2"	310 Lbs.	16 Cu Ft	\$ 4,921	machined to receive $1^{1}/2^{2}$ x $1^{1}/2^{2}$ tubular, 16 gauge steel
FS-RC-48-DA	48" Adder	481/4"	60 ¹ /2"	48 ¹ / ₂ "	230 Lbs.	12 Cu Ft	\$ 4,373	posts.
								BACK PANEL: Back is constructed of 1 ¹ / ₁₆ " thick 3-ply particleboard core with plain sliced veneer both faces, ¹ / ₄ " solid hardwood at top and bottom with eased edges.
								BOTTOM SHELF: Shelf construction consists of ³ / ₄ " thick 3-ply particleboard

